

SAGLAN T-SA 25 (Vn/Vnl/Vs/Vsl/G)



SAGLAN T-SA 25 is a insulation slab made of glass wool for industrial applications, without/with facing Vn/Vnl/Vs/Vsl/G.

Application field

– Technical insulation e.g. ventilation ducts

Note: When used in ventilation ducts, the fixing method must be determined separately by a competent specifier or contractor.

Technical characteristics

Description	Data	Unit	Standard						
Apparent density ρ	approx. 25	kg/m ³	EN 1602						
Reaction to fire without/with facing Vn/Vnl/Vs/Vsl/G.	A1	–	EN 13501-1						
Application temperature	≤ 250	°C	EN 14706						
Test load	250	Pa	EN 14706						
Water vapor diffusion MV1	1	μ	EN 12086						
Thickness tolerance class	T3	mm	EN 823						
Water absorption	WS 1	Kg/m ²	EN 1609						
Impedance (length-related)	> 5 (AF5)	kPa·s/m ²	EN 29053						
Thermal conductivity $\lambda_{N,P}$	T	[°C]	0	50	100	150	200	250	EN 12667
	$\lambda_{N,P}$	[W/mK]	0.033	0.042	0.053	0.065	0.079	0.097	

Delivery types

Thickness (mm)	Width (mm)	Length (mm)	m ² /package	m ² /pallet
20	600	1200	On request	
25	600	1200		
30	600	1200		
40	600	1200		
50	600	1200		
60	600	1200		
80	600	1200		
100	600	1200		
120	600	1200		

Vn = Natural glass fibre fleece, Vnl = Natural glass fibre fleece, long. reinforced, Vs = Black glass fibre fleece, Vsl = Black glass fibre fleece, long. reinforced, G = Black glass fabric

For facings: See datasheet SAGLAN facings



The technical information is based on our present state of knowledge and our experiences. We will not assume any liability for applications in special cases under extraordinary conditions.